

FX3U-FLROM-16/64/64L/1M Hardware Manual

The FX3U-FLROM-16/64/64L/1M memory cassette is a flash memory unit used as program memory for the FX3U/FX3UC PLC.

1. Specifications

✓: Applicable. Check for the version in parentheses.

Model name		FX3U- FLROM-16	FX3U- FLROM-64	FX3U- FLROM-64L	FX3U- FLROM-1M			
Applicable PLC	FX3U PLC	✓	✓	✓	√(Ver.3.00 or later)			
	FX3UC PLC	√(Ver.2.20 or later)	✓	√(Ver.2.20 or later)	√(Ver.3.00 or later)			
Max. memory capacity		16000 steps	64000 steps	64000 steps	*1			
Memory type		Flash memory						
Max. Allowable Write		10000 times						
PROTECT switch		Provided						
Data transfer button		NA	NA	Provided	NA			

64000 steps (program capacity) + 1300KB (symbolic information capacity)


2. Handling Cautions

- For further installation and PROTECT switch details, refer to the User's Manual Hardware Edition of the respective PLC.

 Power off the PLC before attaching/detaching the memory cassette.
 The PLC BRROR (ERR) LED may flicker to indicate a program error when using the product for the first time.
- The PLC ERROR LEW LEB Hisy linker to indicate a program error when using the product for the first time. In such a case, perform an "All Clear" or "Program transfer" by a programming tool. Connect the memory cassette securely to the prescribed connector. A poor connection can cause malfunctions.

 Installing the cassette in a raised or tilted posture can also cause malfunctions.

Cross-section drawing (memory cassette installation condition)
The stage in which the whole









原产地 合格证 日本国 Made in Japan MITSUBISHI ELECTRIC CORPORATION

3. Applicable standard

3. Applicable Standard
FX3U-FLROM-16/64/64/L/1M complies with EC directive (EMC Directive).
Further information can be found in the following manual.
However, FX3U-FLROM-64 made in June, 2005 or later complies with EC directive (EMC Directive). FX3UC-32MT-LT does not comply with EC directive (EMC Directive).

- FX3U Series Hardware Manual (Manual No. JY997D50301)). s Hardware Manual (Manual No. JY997D50301) → FX3UC (D, DS, DSS) Series Hardware Manual (Manual No. JY997D50501)

2MT-LT-2 Hardware Manual (Manual No. JY997D31601) FX3UC-32


Attention This product is designed for use in industrial applications.

(15)

Not N

e lanufactured by: Mitsubishi Electric Corporation 2-7-3 Marunouchi, Chiyoda-ku, Tokyo, 100-8310 Japan

「电器电子产品有害物质限制使用标识要求」的表示方式 Note: This symbol mark is for China only.



含有部品

本产品中所含有的有害6物质的名称, 含有量, 含有部品如 下表所示。 产品中有害物质的名称及含量

方宝物压

部件名称		1月 百 17/00火								
		铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多溴 二苯醚 (PBDE)			
可编程 控制器	外壳	0	0	0	0	0	0			
	印刷基板	X	0	0	0	0	0			
本表格依据SJ/T 11364的规定编制。										

〇:表示该有害物质在该部件所有均质材料中的含量均在GB/T 26572规定的限量要求以下。 ※:表示该有害物质至少在该部件的某一均质材料中的含量超出

GB/T 26572规定的限量要求。

基于中国标准法的参考规格: GB/T15969.2