



APEX DYNAMICS, INC.

**HIGH PRECISION
HIGH SPEED
PLANETARY GEARBOX**

AD / ADR / ADS Series



Stainless




Apex Dynamics, Inc. is the world's most productive manufacturer of servomotor drive planetary gearboxes for precision automation machinery. From our 800,000+ square foot ISO 9001:2008 manufacturing facility, based in Taichung, Taiwan, we manufacture to stock using the newest precision machine tools and quality test and inspection equipment. Complete focus on quality and precision allows us to produce our high quality gearheads at precision levels down to less than 1 arc minute (1/60 th of a degree), with consistency and high reliability.

Based on more than twenty years of accumulated manufacturing and marketing experience, plus the highest level of technical production capabilities, Apex Dynamics, Inc. designs and builds technically advanced, high speed, low backlash servo application planetary gearboxes. Our Break through patented technology (over 6 patents), provides the customer with the optimum high precision helical reducer at a reasonable price. We are continuously improving processes, finding proper and effective methods to provide customers new solutions for difficult applications, and developing new products.

The primary focus in daily operation is quality. We pride ourselves on our dedication to quality; our duty - is customer satisfaction.




AD Series Ordering Code




Ordering Example: AD047-010-P1 / SIEMENS 1FT6 041-4AF71

ADR Series Ordering Code



Ordering Example: ADR047-010-P1 / SIEMENS 1FT5 034-OAK71

ADS Series Ordering Code



Ordering Example: ADS047-010-S1-P1 / SIEMENS 1FT5 034-OAK71



©2019 by APEX DYNAMICS, INC.
 APEX DYNAMICS, INC. reserves modification and copyrights of all technical specifications, illustrations and drawings in this catalog in allowance for continuous products development and advancement.
 For the newest data and information, please visit <http://www.apexdyna.com/>

Specifications / AD Series

Gearbox Performance

| Model No. | | Stage | Ratio ⁽¹⁾ | AD047 | AD064 | AD090 | AD110 | AD140 | AD200 | AD255 |
|--|-----------|-------|----------------------|----------------------------------|--------|-------|-------|--------|--------|--------|
| Nominal Output Torque T_{2N} | Nm | 1 | 4 | 19 | 48 | 130 | 270 | 560 | 1,100 | 1,700 |
| | | | 5 | 22 | 60 | 160 | 330 | 650 | 1,200 | 2,000 |
| | | | 7 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 |
| | | | 10 | 14 | 40 | 100 | 230 | 450 | 900 | 1,500 |
| | | 2 | 20 | 19 | 48 | 130 | 270 | 560 | 1,100 | 1,700 |
| | | | 25 | 22 | 60 | 160 | 330 | 650 | 1,200 | 2,000 |
| | | | 35 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 |
| | | | 40 | 19 | 48 | 130 | 270 | 560 | 1,100 | 1,700 |
| | | | 50 | 22 | 60 | 160 | 330 | 650 | 1,200 | 2,000 |
| | | | 70 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 |
| | | | 100 | 14 | 40 | 100 | 230 | 450 | 900 | 1,500 |
| | | | 16 | 19 | 48 | 130 | 270 | 560 | 1,100 | 1,700 |
| | | | 21 | 22 | 60 | 160 | 330 | 650 | 1,200 | 2,000 |
| | | | 31 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 |
| | | | 61 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 |
| | | | 91 | 14 | 40 | 100 | 230 | 450 | 900 | 1,500 |
| Emergency Stop Torque $T_{2NOT}^{(2)}$ | Nm | 1,2 | 4~100 | 3 times of Nominal Output Torque | | | | | | |
| Nominal Input Speed n_{iN} | rpm | 1,2 | 4~100 | 5,000 | 5,000 | 4,000 | 4,000 | 3,000 | 3,000 | 2,000 |
| Max. Input Speed n_{iB} | rpm | 1,2 | 4~100 | 10,000 | 10,000 | 8,000 | 8,000 | 6,000 | 6,000 | 4,000 |
| Micro Backlash P0 | arcmin | 1 | 4~10 | - | - | ≤1 | ≤1 | ≤1 | ≤1 | ≤1 |
| | | 2 | 20~100 | - | - | - | ≤3 | ≤3 | ≤3 | ≤3 |
| Reduced Backlash P1 | arcmin | 1 | 4~10 | ≤3 | ≤3 | ≤3 | ≤3 | ≤3 | ≤3 | ≤3 |
| | | 2 | 20~100 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 |
| Standard Backlash P2 | arcmin | 1 | 4~10 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 |
| | | 2 | 20~100 | ≤7 | ≤7 | ≤7 | ≤7 | ≤7 | ≤7 | ≤7 |
| Torsional Rigidity | Nm/arcmin | 1,2 | 4~100 | 7 | 13 | 31 | 82 | 151 | 440 | 1,006 |
| Max. Tilting Moment M_{2K} | Nm | 1,2 | 4~100 | 55 | 75 | 190 | 300 | 1,300 | 2,930 | 5,500 |
| Max. Axial Load $F_{2aB}^{(3)}$ | N | 1,2 | 4~100 | 990 | 1,050 | 2,850 | 2,990 | 10,590 | 16,660 | 29,430 |
| Efficiency η | % | 1 | 4~10 | ≥97% | | | | | | |
| | | 2 | 20~100 | ≥94% | | | | | | |
| Weight | kg | 1 | 4~10 | 0.7 | 1.2 | 3.0 | 5.6 | 11.9 | 31.6 | 56.1 |
| | | 2 | 20~100 | 1.0 | 1.6 | 3.7 | 7.3 | 15.9 | 36.9 | 70.4 |
| Operating Temp | °C | 1,2 | 4~100 | -10°C~90°C | | | | | | |
| Lubrication | | | | Synthetic lubrication oils | | | | | | |
| IP Level | | 1,2 | 4~100 | IP65 | | | | | | |
| Mounting Position | | 1,2 | 4~100 | all directions | | | | | | |
| Noise ⁽⁴⁾ | dB(A) | 1,2 | 4~100 | ≤56 | ≤58 | ≤60 | ≤63 | ≤65 | ≤67 | ≤70 |

Gearbox Inertia

| Model No. | | Stage | Ratio ⁽¹⁾ | AD047 | AD064 | AD090 | AD110 | AD140 | AD200 | AD255 |
|--------------------------|----------------------|-------|----------------------|-------|-------|-------|-------|-------|-------|-------|
| Moments of Inertia J_i | kg · cm ² | 1 | 4 | 0.03 | 0.14 | 0.51 | 2.87 | 7.54 | 25.03 | 58.31 |
| | | | 5 | 0.03 | 0.13 | 0.47 | 2.71 | 7.42 | 23.29 | 53.27 |
| | | | 7 | 0.03 | 0.13 | 0.45 | 2.62 | 7.14 | 22.48 | 50.97 |
| | | | 10 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 | 50.56 |
| | | 2 | 20 | 0.03 | 0.03 | 0.13 | 0.47 | 2.71 | 7.42 | 23.29 |
| | | | 25 | 0.03 | 0.03 | 0.13 | 0.47 | 2.71 | 7.42 | 23.29 |
| | | | 35 | 0.03 | 0.03 | 0.13 | 0.47 | 2.71 | 7.42 | 23.29 |
| | | | 40 | 0.03 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 |
| | | | 50 | 0.03 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 |
| | | | 70 | 0.03 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 |
| | | | 100 | 0.03 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 |
| | | | 16 | 0.03 | 0.03 | 0.13 | 0.47 | 2.71 | 7.42 | 23.29 |
| | | | 21 | 0.03 | 0.03 | 0.13 | 0.47 | 2.71 | 7.42 | 23.29 |
| | | | 31 | 0.03 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 |
| | | | 61 | 0.03 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 |
| | | | 91 | 0.03 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 |


(1) Ratio ($i=N_{in}/N_{out}$)(2) Max. acceleration torque $T_{2B} = 60\%$ of T_{2NOT}

(3) Applied to the output shaft center at 100 rpm

(4) The dB values are measured by gearbox with ratio 10 (1-stage) or ratio 100 (2-stage), no loading at 3,000 RPM or at the respective Nominal Input Speed by bigger model size.

By lower ratio and/or higher RPM, the noise level could be 3 to 5 dB higher.

Dimensions (1-stage, Ratio $i=4\sim 10$) / AD Series




[unit: mm]

| Dimension | AD047 | AD064 | AD090 | AD110 | AD140 | AD200 | AD255 |
|-------------------|------------------------|------------------------|-------------|--------------|-----------------|-----------------|---------------|
| D1 _{H7} | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D2 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D3 _{H7} | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D4 _{H7} | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D5 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D6 | 4 x M3 x 0.5P | 7 x M5 x 0.8P | 7 x M6 x 1P | 11 x M6 x 1P | 11 x M8 x 1.25P | 11 x M10 x 1.5P | 12 x M16 x 2P |
| D7 | 72 | 86 | 118 | 145 | 179 | 247 | 300 |
| D8 _{H7} | 3 | 5 | 6 | 6 | 8 | 10 | 12 |
| D9 | 45.5 | 55 | 77 | 90 | 113 | 138 | 175 |
| D10 | 8 x 3.4 | 8 x 4.5 | 8 x 5.5 | 8 x 5.5 | 12 x 6.6 | 12 x 9 | 16 x 13.5 |
| D11 _{H7} | 60 | 70 | 95 | 120 | 152 | 212 | 255 |
| D12 | 46.2 | 63.2 | 89.2 | 109.2 | 139.2 | 199.2 | 254.2 |
| L1 | 4 | 8 | 12 | 12 | 12 | 16 | 20 |
| L2 | 6.5 | 8 | 13.5 | 13.5 | 17 | 22.5 | 30.5 |
| L3 | 3 | 3 | 6 | 6 | 6 | 8 | 12 |
| L4 | 19.5 | 19.5 | 30 | 29 | 38 | 50 | 66 |
| L5 | 7 | 7 | 10 | 10 | 14.6 | 15 | 20 |
| L6 | 4 | 4 | 7 | 8 | 10 | 12 | 18 |
| L7 | 5 | 7.7 | 8 | 10 | 12 | 15 | 20 |
| L8 | 18.5 | 28.5 | 27 | 37 | 62 | 69.5 | 82 |
| L9 | 4 | 6 | 7 | 7 | 7 | 10 | 10 |
| L10 | 0.5 | 0.5 | 1 | 1 | 1 | 1 | 1 |
| C1 ¹ | 46 | 70 | 100 | 130 | 165 | 215 | 235 |
| C2 ¹ | M4 x 0.7P | M5 x 0.8P | M6 x 1P | M8 x 1.25P | M10 x 1.5P | M12 x 1.75P | M12 x 1.75P |
| C3 ¹ | ≤11 / ≤12 ² | ≤14 / ≤16 ² | ≤19 / ≤24 | ≤32 | ≤38 | ≤48 | ≤55 |
| C4 ¹ | 30 | 34 | 40 | 50 | 60 | 85 | 116 |
| C5 ¹ | 30 | 50 | 80 | 110 | 130 | 180 | 200 |
| C6 ¹ | 3.5 | 8 | 4 | 5 | 6 | 6 | 6 |
| C7 ¹ | 48 | 60 | 90 | 115 | 142 | 190 | 220 |
| C8 ¹ | 19.5 | 19 | 17 | 19.5 | 22.5 | 29 | 63 |
| C9 ¹ | 70 | 82.5 | 99.5 | 121.5 | 151 | 199.5 | 256.5 |
| C10 ¹ | 13.25 | 13.5 | 10.75 | 13 | 15 | 20.75 | 53.5 |
| OD | 56 x 2 | 66 x 2 | 90 x 3 | 110 x 3 | 145 x 3 | 200 x 5 | 238 x 5 |

1. C1~C10 are motor specific dimensions (metric std shown). Refer to www.apexdyna.com and Design Tool to view your specific motor mounting system.
 2. AD047 ratio 5, 10 offers C3 ≤ 12 option; AD064 ratio 5, 10 offers C3 ≤ 16 option.

Dimensions (2-stage, Ratio $i=20\sim 100$) / AD Series




[unit: mm]

| Dimension | AD047 | AD064 | AD090 | AD110 | AD140 | AD200 | AD255 |
|-------------------|---------------|---------------|---------------------|--------------|-----------------|-----------------|---------------|
| D1 _{H7} | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D2 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D3 _{H7} | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D4 _{H7} | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D5 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D6 | 4 x M3 x 0.5P | 7 x M5 x 0.8P | 7 x M6 x 1P | 11 x M6 x 1P | 11 x M8 x 1.25P | 11 x M10 x 1.5P | 12 x M16 x 2P |
| D7 | 72 | 86 | 118 | 145 | 179 | 247 | 300 |
| D8 _{H7} | 3 | 5 | 6 | 6 | 8 | 10 | 12 |
| D9 | 45.5 | 45.5 | 53.4 | 77 | 102 | 125 | 160 |
| D10 | 8 x 3.4 | 8 x 4.5 | 8 x 5.5 | 8 x 5.5 | 12 x 6.6 | 12 x 9 | 16 x 13.5 |
| D11 _{H7} | 60 | 70 | 95 | 120 | 152 | 212 | 255 |
| D12 | 46.2 | 63.2 | 89.2 | 109.2 | 139.2 | 199.2 | 254.2 |
| L1 | 4 | 8 | 12 | 12 | 12 | 16 | 20 |
| L2 | 6.5 | 8 | 13.5 | 13.5 | 17 | 22.5 | 30.5 |
| L3 | 3 | 3 | 6 | 6 | 6 | 8 | 12 |
| L4 | 19.5 | 19.5 | 30 | 29 | 38 | 50 | 66 |
| L5 | 7 | 7 | 10 | 10 | 14.6 | 15 | 20 |
| L6 | 4 | 4 | 7 | 8 | 10 | 12 | 18 |
| L7 | 5 | 7.7 | 8 | 10 | 12 | 15 | 20 |
| L8 | 54.5 | 65 | 60 | 87.5 | 110 | 132.5 | 148 |
| L9 | 4 | 6 | 7 | 7 | 7 | 10 | 10 |
| L10 | 0.5 | 0.5 | 1 | 1 | 1 | 1 | 1 |
| C1 ³ | 46 | 46 | 70 | 100 | 130 | 165 | 215 |
| C2 ³ | M4 x 0.7P | M4 x 0.7P | M5 x 0.8P | M6 x 1P | M8 x 1.25P | M10 x 1.5P | M12 x 1.75P |
| C3 ³ | ≤11 / ≤12 | ≤11 / ≤12 | ≤14 / ≤15.875 / ≤16 | ≤19 / ≤24 | ≤32 | ≤38 | ≤48 |
| C4 ³ | 30 | 30 | 34 | 40 | 50 | 60 | 85 |
| C5 ³ | 30 | 30 | 50 | 80 | 110 | 130 | 180 |
| C6 ³ | 3.5 | 3.5 | 8 | 4 | 5 | 6 | 6 |
| C7 ³ | 48 | 48 | 60 | 90 | 115 | 142 | 190 |
| C8 ³ | 19.5 | 19.5 | 19 | 17 | 19.5 | 22.5 | 29 |
| C9 ³ | 97.5 | 108 | 134 | 160 | 204 | 248 | 311.5 |
| C10 ³ | 13.25 | 13.25 | 13.5 | 10.75 | 13 | 15 | 20.75 |
| OD | 56 x 2 | 66 x 2 | 90 x 3 | 110 x 3 | 145 x 3 | 200 x 5 | 238 x 5 |

3. C1-C10 are motor specific dimensions (metric std shown). Refer to www.apexdyna.com and Design Tool to view your specific motor mounting system.

Dimensions (2-stage, Ratio $i = 16 \sim 91$) / AD Series



[unit: mm]

| Dimension | AD047 | AD064 | AD090 | AD110 | AD140 | AD200 | AD255 |
|-------------------|---------------|---------------|---------------------|--------------|-----------------|-----------------|---------------|
| D1 ^{H7} | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D2 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D3 ^{h7} | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D4 ^{h7} | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D5 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D6 | 4 x M3 x 0.5P | 7 x M5 x 0.8P | 7 x M6 x 1P | 11 x M6 x 1P | 11 x M8 x 1.25P | 11 x M10 x 1.5P | 12 x M16 x 2P |
| D7 | 72 | 86 | 118 | 145 | 179 | 247 | 300 |
| D8 ^{H7} | 3 | 5 | 6 | 6 | 8 | 10 | 12 |
| D9 | 45.5 | 45.5 | 55 | 77 | 90 | 113 | 138 |
| D10 | 8 x 3.4 | 8 x 4.5 | 8 x 5.5 | 8 x 5.5 | 12 x 6.6 | 12 x 9 | 16 x 13.5 |
| D11 ^{h7} | 60 | 70 | 95 | 120 | 152 | 212 | 255 |
| D18 | 46.2 | 63.2 | 89.2 | 109.2 | 139.2 | 199.2 | 254.2 |
| L1 | 4 | 8 | 12 | 12 | 12 | 16 | 20 |
| L2 | 6.5 | 8 | 13.5 | 13.5 | 17 | 22.5 | 30.5 |
| L3 | 3 | 3 | 6 | 6 | 6 | 8 | 12 |
| L4 | 19.5 | 19.5 | 30 | 29 | 38 | 50 | 66 |
| L5 | 7 | 7 | 10 | 10 | 14.6 | 15 | 20 |
| L6 | 4 | 4 | 7 | 8 | 10 | 12 | 18 |
| L7 | 5 | 7.7 | 8 | 10 | 12 | 15 | 20 |
| L8 | 52.5 | 28.5 | 32 | 37 | 122 | 79.5 | 82 |
| L9 | 4 | 6 | 7 | 7 | 7 | 10 | 10 |
| L10 | 0.5 | 0.5 | 1 | 1 | 1 | 1 | 1 |
| C1 ⁴ | 46 | 46 | 70 | 100 | 130 | 165 | 215 |
| C2 ⁴ | M4 x 0.7P | M4 x 0.7P | M5 x 0.8P | M6 x 1P | M8 x 1.25P | M10 x 1.5P | M12 x 1.75P |
| C3 ⁴ | ≤11 / ≤12 | ≤11 / ≤12 | ≤14 / ≤15.875 / ≤16 | ≤19 / ≤24 | ≤32 | ≤38 | ≤48 |
| C4 ⁴ | 30 | 30 | 34 | 40 | 50 | 60 | 85 |
| C5 ⁴ | 30 | 30 | 50 | 80 | 110 | 130 | 180 |
| C6 ⁴ | 3.5 | 3.5 | 8 | 4 | 5 | 6 | 6 |
| C7 ⁴ | 48 | 48 | 60 | 90 | 115 | 142 | 190 |
| C8 ⁴ | 19.5 | 19.5 | 19 | 17 | 19.5 | 22.5 | 29 |
| C9 ⁴ | 100 | 106 | 130.5 | 149 | 205 | 247.5 | 323 |
| C10 ⁴ | 13.25 | 13.25 | 13.5 | 10.75 | 13 | 15 | 20.75 |
| OD | 56 x 2 | 66 x 2 | 90 x 3 | 110 x 3 | 145 x 3 | 200 x 5 | 238 x 5 |

4. C1~C10 are motor specific dimensions (metric std shown). Refer to www.apexdyna.com and Design Tool to view your specific motor mounting system.

Specifications / ADR Series

Gearbox Performance

| Model No. | | Stage | Ratio ⁽¹⁾ | ADR047 | ADR064 | ADR090 | ADR110 | ADR140 | ADR200 | ADR255 | |
|--|-----------|-------|----------------------|----------------------------------|--------|--------|--------|--------|--------|--------|---|
| Nominal Output Torque T_{2N} | Nm | 1 | 4 | 19 | 48 | 130 | 270 | 560 | 1,100 | 1,700 | |
| | | | 5 | 22 | 60 | 160 | 330 | 650 | 1,200 | 2,000 | |
| | | | 7 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 | |
| | | | 10 | 14 | 60 | 160 | 325 | 650 | 1,200 | 2,000 | |
| | | | 14 | - | 42 | 140 | 300 | 550 | 1,100 | 1,800 | |
| | | | 20 | - | 40 | 100 | 230 | 450 | 900 | 1,500 | |
| | | 2 | 20 | 19 | - | - | - | - | - | - | - |
| | | | 25 | 22 | 60 | 160 | 330 | 650 | 1,200 | 2,000 | |
| | | | 35 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 | |
| | | | 40 | 19 | 48 | 130 | 270 | 560 | 1,100 | 1,700 | |
| | | | 50 | 22 | 60 | 160 | 330 | 650 | 1,200 | 2,000 | |
| | | | 70 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 | |
| | | | 100 | 14 | 40 | 100 | 230 | 450 | 900 | 1,500 | |
| | | | 140 | - | - | 140 | 300 | 550 | 1,100 | 1,800 | |
| 200 | - | - | 100 | 230 | 450 | 900 | 1,500 | | | | |
| Emergency Stop Torque T_{2NOTB} ⁽²⁾ | Nm | 1,2 | 4~200 | 3 times of Nominal Output Torque | | | | | | | |
| Nominal Input Speed n_{1N} | rpm | 1,2 | 4~200 | 5,000 | 5,000 | 4,000 | 4,000 | 3,000 | 3,000 | 2,000 | |
| Max. Input Speed n_{1B} | rpm | 1,2 | 4~200 | 10,000 | 10,000 | 8,000 | 8,000 | 6,000 | 6,000 | 4,000 | |
| Micro Backlash P0 | arcmin | 1 | 4~20 | - | - | ≤2 | ≤2 | ≤2 | ≤2 | ≤2 | |
| | | 2 | 25~200 | - | - | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 | |
| Reduced Backlash P1 | arcmin | 1 | 4~20 | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 | |
| | | 2 | 25~200 | ≤7 | ≤7 | ≤7 | ≤7 | ≤7 | ≤7 | ≤7 | |
| Standard Backlash P2 | arcmin | 1 | 4~20 | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 | |
| | | 2 | 25~200 | ≤9 | ≤9 | ≤9 | ≤9 | ≤9 | ≤9 | ≤9 | |
| Torsional Rigidity | Nm/arcmin | 1,2 | 4~200 | 7 | 13 | 31 | 82 | 151 | 440 | 1,006 | |
| Max. Tilting Moment M_{2K} | Nm | 1,2 | 4~200 | 55 | 75 | 190 | 300 | 1,300 | 2,930 | 5,500 | |
| Max. Axial Load F_{2aB} ⁽³⁾ | N | 1,2 | 4~200 | 990 | 1,050 | 2,850 | 2,990 | 10,590 | 16,660 | 29,430 | |
| Efficiency η | % | 1 | 4~20 | ≥95% | | | | | | | |
| | | 2 | 25~200 | ≥92% | | | | | | | |
| Weight | kg | 1 | 4~20 | 1.1 | 2.1 | 5.9 | 10.5 | 21.9 | 50.9 | 85.4 | |
| | | 2 | 25~200 | 1.4 | 1.9 | 4.5 | 9.8 | 20.1 | 45.4 | 85.9 | |
| Operating Temp | °C | 1,2 | 4~200 | -10°C~90°C | | | | | | | |
| Lubrication | | | | Synthetic lubrication oils | | | | | | | |
| IP Level | | 1,2 | 4~200 | IP65 | | | | | | | |
| Mounting Position | | 1,2 | 4~200 | all directions | | | | | | | |
| Noise ⁽⁴⁾ | dB(A) | 1,2 | 4~200 | ≤61 | ≤63 | ≤65 | ≤68 | ≤70 | ≤72 | ≤74 | |

Gearbox Inertia

| Model No. | | Stage | Ratio ⁽¹⁾ | ADR047 | ADR064 | ADR090 | ADR110 | ADR140 | ADR200 | ADR255 |
|--------------------------|----------------------|-------|----------------------|--------|--------|--------|--------|--------|--------|--------|
| Moments of Inertia J_i | kg · cm ² | 1 | 4~10 | 0.09 | 0.35 | 2.25 | 6.84 | 23.4 | 68.9 | 135.4 |
| | | | 14 | - | 0.31 | 1.87 | 6.25 | 21.8 | 65.6 | 119.8 |
| | | | 20 | - | 0.31 | 1.87 | 6.25 | 21.8 | 65.6 | 119.8 |
| | | 2 | 20 | 0.09 | - | - | - | - | - | - |
| | | | 25~100 | 0.09 | 0.09 | 0.35 | 2.25 | 6.84 | 23.4 | 68.9 |
| | | | 140~200 | - | - | 0.31 | 1.87 | 6.25 | 21.8 | 65.6 |


(1) Ratio ($i=N_{in}/N_{out}$)(2) Max. acceleration torque $T_{2B} = 60\%$ of T_{2NOT}

(3) Applied to the output shaft center at 100 rpm

(4) The dB values are measured by gearbox with ratio 10 (1-stage) or ratio 100 (2-stage), no loading at 3,000 RPM or at the respective Nominal Input Speed by bigger model size.

By lower ratio and/or higher RPM, the noise level could be 3 to 5 dB higher.

Dimensions (1-stage, Ratio $i=4\sim 20$) / ADR Series




[unit: mm]

| Dimension | ADR047 | ADR064 | ADR090 | ADR110 | ADR140 | ADR200 | ADR255 |
|------------------|---------------|---------------|-------------|--------------|-----------------|-----------------|---------------|
| D1 _{H7} | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D2 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D3 _{h7} | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D4 _{h7} | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D5 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D6 | 4 x M3 x 0.5P | 7 x M5 x 0.8P | 7 x M6 x 1P | 11 x M6 x 1P | 11 x M8 x 1.25P | 11 x M10 x 1.5P | 12 x M16 x 2P |
| D7 | 72 | 86 | 118 | 145 | 179 | 247 | 300 |
| D8 _{H7} | 3 | 5 | 6 | 6 | 8 | 10 | 12 |
| D10 | 8 x 3.4 | 8 x 4.5 | 8 x 5.5 | 8 x 5.5 | 12 x 6.6 | 12 x 9 | 16 x 13.5 |
| D12 | 46.2 | 63.2 | 89.2 | 109.2 | 139.2 | 199.2 | 254.2 |
| L1 | 4 | 8 | 12 | 12 | 12 | 16 | 20 |
| L2 | 6.5 | 8 | 13.5 | 13.5 | 17 | 22.5 | 30.5 |
| L3 | 3 | 3 | 6 | 6 | 6 | 8 | 12 |
| L4 | 19.5 | 19.5 | 30 | 29 | 38 | 50 | 66 |
| L5 | 7 | 7 | 10 | 10 | 14.6 | 15 | 20 |
| L6 | 4 | 4 | 7 | 8 | 10 | 12 | 18 |
| L8 | 107.5 | 126 | 172.5 | 201 | 263.5 | 334.5 | 392 |
| L9 | 4 | 6 | 7 | 7 | 7 | 10 | 10 |
| L10 | 0.5 | 0.5 | 1 | 1 | 1 | 1 | 1 |
| C1 ¹ | 46 | 70 | 100 | 130 | 165 | 215 | 235 |
| C2 ¹ | M4 x 0.7P | M5 x 0.8P | M6 x 1P | M8 x 1.25P | M10 x 1.5P | M12 x 1.75P | M12 x 1.75P |
| C3 ¹ | ≤11 / ≤12 | ≤14 / ≤16 | ≤19 / ≤24 | ≤32 | ≤38 | ≤48 | ≤55 |
| C4 ¹ | 30 | 34 | 40 | 50 | 60 | 85 | 116 |
| C5 ¹ | 30 | 50 | 80 | 110 | 130 | 180 | 200 |
| C6 ¹ | 3.5 | 8 | 4 | 5 | 6 | 6 | 6 |
| C7 ¹ | 48 | 60 | 90 | 115 | 142 | 190 | 220 |
| C8 ¹ | 19.5 | 19 | 17 | 19.5 | 22.5 | 29 | 63 |
| C9 ¹ | 104.25 | 116.5 | 159.5 | 199 | 245.5 | 316 | 398.5 |
| C10 ¹ | 13.25 | 13.5 | 10.75 | 13 | 15 | 20.75 | 53.5 |
| C11 ¹ | 74 | 81.5 | 107.5 | 134 | 164.5 | 213.5 | 268.5 |

1. C1~C10 are motor specific dimensions (metric std shown). Refer to www.apexdyna.com and Design Tool to view your specific motor mounting system.

Dimensions (2-stage, Ratio $i=25\sim 200$) / ADR Series



[unit: mm]

| Dimension | ADR047 | ADR064 | ADR090 | ADR110 | ADR140 | ADR200 | ADR255 |
|------------------|---------------|---------------|---------------------|--------------|-----------------|-----------------|---------------|
| D1 _{H7} | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D2 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D3 _{h7} | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D4 _{h7} | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D5 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D6 | 4 x M3 x 0.5P | 7 x M5 x 0.8P | 7 x M6 x 1P | 11 x M6 x 1P | 11 x M8 x 1.25P | 11 x M10 x 1.5P | 12 x M16 x 2P |
| D7 | 72 | 86 | 118 | 145 | 179 | 247 | 300 |
| D8 _{H7} | 3 | 5 | 6 | 6 | 8 | 10 | 12 |
| D10 | 8 x 3.4 | 8 x 4.5 | 8 x 5.5 | 8 x 5.5 | 12 x 6.6 | 12 x 9 | 16 x 13.5 |
| D12 | 46.2 | 63.2 | 89.2 | 109.2 | 139.2 | 199.2 | 254.2 |
| L1 | 4 | 8 | 12 | 12 | 12 | 16 | 20 |
| L2 | 6.5 | 8 | 13.5 | 13.5 | 17 | 22.5 | 30.5 |
| L3 | 3 | 3 | 6 | 6 | 6 | 8 | 12 |
| L4 | 19.5 | 19.5 | 30 | 29 | 38 | 50 | 66 |
| L5 | 7 | 7 | 10 | 10 | 14.6 | 15 | 20 |
| L6 | 4 | 4 | 7 | 8 | 10 | 12 | 18 |
| L8 | 122 | 132.5 | 163 | 217.5 | 269.5 | 333.5 | 403 |
| L9 | 4 | 6 | 7 | 7 | 7 | 10 | 10 |
| L10 | 0.5 | 0.5 | 1 | 1 | 1 | 1 | 1 |
| C1 ² | 46 | 46 | 70 | 100 | 130 | 165 | 215 |
| C2 ² | M4 x 0.7P | M4 x 0.7P | M5 x 0.8P | M6 x 1P | M8 x 1.25P | M10 x 1.5P | M12 x 1.75P |
| C3 ² | ≤11 / ≤12 | ≤11 / ≤12 | ≤14 / ≤15.875 / ≤16 | ≤19 / ≤24 | ≤32 | ≤38 | ≤48 |
| C4 ² | 30 | 30 | 34 | 40 | 50 | 60 | 85 |
| C5 ² | 30 | 30 | 50 | 80 | 110 | 130 | 180 |
| C6 ² | 3.5 | 3.5 | 8 | 4 | 5 | 6 | 6 |
| C7 ² | 48 | 48 | 60 | 90 | 115 | 142 | 190 |
| C8 ² | 19.5 | 19.5 | 19 | 17 | 19.5 | 22.5 | 29 |
| C9 ² | 103.25 | 108.25 | 128.25 | 166.5 | 209 | 269.5 | 340 |
| C10 ² | 13.25 | 13.25 | 13.5 | 10.75 | 13 | 15 | 20.75 |
| C11 ² | 74 | 74 | 81.5 | 107.5 | 134 | 164.5 | 213.5 |

2. C1-C10 are motor specific dimensions (metric std shown). Refer to www.apexdyna.com and Design Tool to view your specific motor mounting system.

Specifications / ADS Series

Gearbox Performance

| Model No. | Stage | Ratio ⁽¹⁾ | ADS047 | ADS064 | ADS090 | ADS110 | ADS140 | ADS200 | ADS255 | |
|--|-----------|--|--------|----------------------------|--------|----------------------------------|--------|--------|--------|--------|
| Nominal Output Torque T_{2N} | 1 | 4 | 19 | 48 | 130 | 270 | 560 | 1,100 | 1,700 | |
| | | 5 | 22 | 60 | 160 | 330 | 650 | 1,200 | 2,000 | |
| | | 7 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 | |
| | | 10 | 14 | 40 | 100 | 230 | 450 | 900 | 1,500 | |
| | 2 | 16 | 19 | 48 | 130 | 270 | 560 | 1,100 | 1,700 | |
| | | 21 | 22 | 60 | 160 | 330 | 650 | 1,200 | 2,000 | |
| | | 31 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 | |
| | | 61 | 19 | 50 | 140 | 300 | 550 | 1,100 | 1,800 | |
| | | 91 | 14 | 40 | 100 | 230 | 450 | 900 | 1,500 | |
| | | Emergency Stop Torque $T_{2NOT}^{(2)}$ | Nm | 1,2 | 4~91 | 3 times of Nominal Output Torque | | | | |
| Nominal Input Speed n_{1N} | rpm | 1,2 | 4~91 | 5,000 | 5,000 | 4,000 | 4,000 | 3,000 | 3,000 | 2,000 |
| Max. Input Speed n_{1B} | rpm | 1,2 | 4~91 | 10,000 | 10,000 | 8,000 | 7,500 | 4,500 | 4,500 | 3,800 |
| Micro Backlash P0 | arcmin | 1 | 4~10 | - | - | ≤1 | ≤1 | ≤1 | ≤1 | ≤1 |
| | | 2 | 16~91 | - | - | - | ≤3 | ≤3 | ≤3 | ≤3 |
| Reduced Backlash P1 | arcmin | 1 | 4~10 | ≤3 | ≤3 | ≤3 | ≤3 | ≤3 | ≤3 | ≤3 |
| | | 2 | 16~91 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 |
| Standard Backlash P2 | arcmin | 1 | 4~10 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 | ≤5 |
| | | 2 | 16~91 | ≤7 | ≤7 | ≤7 | ≤7 | ≤7 | ≤7 | ≤7 |
| Torsional Rigidity | Nm/arcmin | 1,2 | 4~91 | 3 | 7 | 14 | 25 | 50 | 145 | 225 |
| Max. Tilting Moment M_{2K} | Nm | 1,2 | 4~91 | 55 | 75 | 190 | 300 | 1,300 | 2,930 | 5,500 |
| Max. Axial Load | N | 1,2 | 4~91 | 990 | 1,050 | 2,850 | 2,990 | 10,590 | 16,660 | 29,430 |
| Input Max. Radial Load $F_{1rB}^{(3)}$ | N | 1 | 4~10 | 165 | 395 | 1,300 | 1,525 | 2,800 | 4,500 | 12,500 |
| | | 2 | 16~91 | 165 | 165 | 395 | 1,300 | 1,525 | 2,800 | 4,500 |
| Input Max. Axial Load $F_{1aB}^{(3)}$ | N | 1 | 4~10 | 580 | 1,000 | 1,100 | 980 | 2,700 | 4,700 | 8,000 |
| | | 2 | 16~91 | 580 | 580 | 1,000 | 1,100 | 980 | 2,700 | 4,700 |
| Efficiency η | % | 1 | 4~10 | ≥97% | | | | | | |
| | | 2 | 16~91 | ≥94% | | | | | | |
| Weight | kg | 1 | 4~10 | 0.8 | 1.4 | 3.4 | 6.7 | 13.5 | 35.0 | 63.8 |
| | | 2 | 16~91 | 1.1 | 1.6 | 4.0 | 7.3 | 16.6 | 36.4 | 74.7 |
| Operating Temp | °C | 1,2 | 4~91 | -10°C~90°C | | | | | | |
| Lubrication | | | | Synthetic lubrication oils | | | | | | |
| IP Level | | 1,2 | 4~91 | IP65 | | | | | | |
| Mounting Position | | 1,2 | 4~91 | all directions | | | | | | |
| Noise ⁽⁴⁾ | dB(A) | 1,2 | 4~91 | ≤56 | ≤58 | ≤60 | ≤63 | ≤65 | ≤67 | ≤70 |

Gearbox Inertia

| Model No. | Stage | Ratio ⁽¹⁾ | ADS047 | ADS064 | ADS090 | ADS110 | ADS140 | ADS200 | ADS255 |
|--------------------------|-------|----------------------|--------|--------|--------|--------|--------|--------|--------|
| Moments of Inertia J_1 | 1 | 4 | 0.06 | 0.21 | 0.87 | 3.65 | 10.27 | 43.05 | 102.68 |
| | | 5 | 0.06 | 0.21 | 0.83 | 3.53 | 10.17 | 41.76 | 99.12 |
| | | 7 | 0.06 | 0.21 | 0.82 | 3.47 | 9.99 | 41.15 | 97.41 |
| | | 10 | 0.06 | 0.21 | 0.81 | 3.45 | 9.93 | 40.97 | 97.03 |
| | 2 | 16 | 0.06 | 0.06 | 0.21 | 0.83 | 3.53 | 10.17 | 41.76 |
| | | 21 | 0.06 | 0.06 | 0.21 | 0.83 | 3.53 | 10.17 | 41.76 |
| | | 31 | 0.06 | 0.06 | 0.21 | 0.83 | 3.53 | 10.17 | 41.76 |
| | | 61 | 0.06 | 0.06 | 0.21 | 0.81 | 3.45 | 9.93 | 40.97 |
| | | 91 | 0.06 | 0.06 | 0.21 | 0.81 | 3.45 | 9.93 | 40.97 |
| | | | | | | | | | |

(1) Ratio ($i=N_{in}/N_{out}$)


(2) Max. acceleration torque $T_{2B} = 60\%$ of T_{2NOT}

(3) Applied to the output shaft center at 100 rpm

(4) The dB values are measured by gearbox with ratio 10 (1-stage) or ratio 100 (2-stage), no loading at 3,000 RPM or at the respective Nominal Input Speed by bigger model size.

By lower ratio and/or higher RPM, the noise level could be 3 to 5 dB higher.


Dimensions (1-stage, Ratio $i=4\sim 10$) / ADS Series



[unit: mm]

| Dimension | ADS047 | ADS064 | ADS090 | ADS110 | ADS140 | ADS200 | ADS255 |
|-------------------|---------------|---------------|-------------|--------------|-----------------|-----------------|---------------|
| D1 _{h7} | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D2 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D3 _{h7} | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D4 _{h7} | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D5 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D6 | 4 x M3 x 0.5P | 7 x M5 x 0.8P | 7 x M6 x 1P | 11 x M6 x 1P | 11 x M8 x 1.25P | 11 x M10 x 1.5P | 12 x M16 x 2P |
| D7 | 72 | 86 | 118 | 145 | 179 | 247 | 300 |
| D8 _{h7} | 3 | 5 | 6 | 6 | 8 | 10 | 12 |
| D9 | 43 | 55 | 78 | 100 | 125 | 175 | 210 |
| D10 | 8 x 3.4 | 8 x 4.5 | 8 x 5.5 | 8 x 5.5 | 12 x 6.6 | 12 x 9 | 16 x 13.5 |
| D11 _{h7} | 60 | 70 | 95 | 120 | 152 | 212 | 255 |
| D12 | 31 | 22 | 22 | 30 | 40 | 75 | 95 |
| D13 | 37 | 50 | 62 | 82 | 108 | 145 | 172 |
| D14 | M4 x 0.7P | M4 x 0.7P | M5 x 0.8P | M8 x 1.25P | M12 x 1.75P | M16 x 2P | M20 x 2.5P |
| D15 | M3 x 0.5P | M3 x 0.5P | M4 x 0.7P | M5 x 0.8P | M6 x 1P | M8 x 1.25P | M8 x 1.25P |
| D16 | 51.5 | 61.5 | 84 | 107 | 137 | 193 | 235 |
| D17 _{k6} | 11 | 14 | 16 | 22 | 32 | 40 | 55 |
| D18 | 46.2 | 63.2 | 89.2 | 109.2 | 139.2 | 199.2 | 254.2 |
| L1 | 4 | 8 | 12 | 12 | 12 | 16 | 20 |
| L2 | 6.5 | 8 | 13.5 | 13.5 | 17 | 22.5 | 30.5 |
| L3 | 3 | 3 | 6 | 6 | 6 | 8 | 12 |
| L4 | 19.5 | 19.5 | 30 | 29 | 38 | 50 | 66 |
| L5 | 7 | 7 | 10 | 10 | 14.6 | 15 | 20 |
| L6 | 4 | 4 | 7 | 8 | 10 | 12 | 18 |
| L7 | 5 | 7.7 | 8 | 10 | 12 | 15 | 20 |
| L8 | 32.5 | 43.5 | 47 | 62 | 72 | 89.5 | 112 |
| L9 | 4 | 6 | 7 | 7 | 7 | 10 | 10 |
| L10 | 0.5 | 0.5 | 1 | 1 | 1 | 1 | 1 |
| L11 | 89.5 | 110.5 | 138.5 | 170 | 218 | 296 | 372.5 |
| L12 | 18 | 22 | 28 | 36 | 58 | 82 | 115 |
| L13 | 2.5 | 2.5 | 3.5 | 3.5 | 3.5 | 4.5 | 4.5 |
| L14 | 10 | 10 | 12.5 | 19 | 28 | 36 | 42 |
| L15 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 |
| L16 | 5.5 | 5.5 | 7 | 9 | 11 | 14 | 14 |
| L17 | 2 | 2 | 3 | 3 | 6 | 6 | 7 |
| L18 | 14 | 18 | 22 | 28 | 45 | 70 | 90 |
| B1 _{h9} | 4 | 5 | 5 | 6 | 10 | 12 | 16 |
| H1 | 12.5 | 16 | 18 | 24.5 | 35 | 43 | 59 |
| OD | 56 x 2 | 66 x 2 | 90 x 3 | 110 x 3 | 145 x 3 | 200 x 5 | 238 x 5 |
| V | 4 | 4 | 4 | 4 | 6 | 6 | 6 |
| Z | 45 | 45 | 45 | 45 | 30 | 30 | 30 |

Dimensions (2-stage, Ratio i= 16~91) / ADS Series




[unit: mm]


| Dimension | ADS047 | ADS064 | ADS090 | ADS110 | ADS140 | ADS200 | ADS255 |
|-------------------|---------------|---------------|-------------|--------------|-----------------|-----------------|---------------|
| D1 _{H7} | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D2 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D3 _{H7} | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D4 _{H7} | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D5 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D6 | 4 x M3 x 0.5P | 7 x M5 x 0.8P | 7 x M6 x 1P | 11 x M6 x 1P | 11 x M8 x 1.25P | 11 x M10 x 1.5P | 12 x M16 x 2P |
| D7 | 72 | 86 | 118 | 145 | 179 | 247 | 300 |
| D8 _{H7} | 3 | 5 | 6 | 6 | 8 | 10 | 12 |
| D9 | 43 | 48 | 68 | 86 | 110 | 132 | 182 |
| D10 | 8 x 3.4 | 8 x 4.5 | 8 x 5.5 | 8 x 5.5 | 12 x 6.6 | 12 x 9 | 16 x 13.5 |
| D11 _{H7} | 60 | 70 | 95 | 120 | 152 | 212 | 255 |
| D12 | 22 | 22 | 22 | 22 | 30 | 40 | 75 |
| D13 | 37 | 37 | 50 | 62 | 82 | 108 | 145 |
| D14 | M4 x 0.7P | M4 x 0.7P | M4 x 0.7P | M5 x 0.8P | M8 x 1.25P | M12 x 1.75P | M16 x 2P |
| D15 | M3 x 0.5P | M3 x 0.5P | M4 x 0.7P | M5 x 0.8P | M6 x 1P | M8 x 1.25P | M10 x 1.5P |
| D16 | 51.5 | 61.5 | 84 | 107 | 137 | 193 | 235 |
| D17 _{K6} | 11 | 11 | 14 | 16 | 22 | 32 | 40 |
| D18 | 46.2 | 63.2 | 89.2 | 109.2 | 139.2 | 199.2 | 254.2 |
| L1 | 4 | 8 | 12 | 12 | 12 | 16 | 20 |
| L2 | 6.5 | 8 | 13.5 | 13.5 | 17 | 22.5 | 30.5 |
| L3 | 3 | 3 | 6 | 6 | 6 | 8 | 12 |
| L4 | 19.5 | 19.5 | 30 | 29 | 38 | 50 | 66 |
| L5 | 7 | 7 | 10 | 10 | 14.6 | 15 | 20 |
| L6 | 4 | 4 | 7 | 8 | 10 | 12 | 18 |
| L7 | 5 | 7.7 | 8 | 10 | 12 | 15 | 20 |
| L8 | 62.5 | 63.5 | 67 | 82 | 122 | 79.5 | 177 |
| L9 | 4 | 6 | 7 | 7 | 7 | 10 | 10 |
| L10 | 0.5 | 0.5 | 1 | 1 | 1 | 1 | 1 |
| L11 | 119.5 | 125.5 | 158.5 | 188 | 253.5 | 314.5 | 419.5 |
| L12 | 18 | 18 | 22 | 28 | 36 | 58 | 82 |
| L13 | 2.5 | 2.5 | 2.5 | 3.5 | 3.5 | 3.5 | 4.5 |
| L14 | 10 | 10 | 10 | 12.5 | 19 | 28 | 36 |
| L15 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 |
| L16 | 5.5 | 5.5 | 7 | 9 | 11 | 14 | 18 |
| L17 | 2 | 2 | 2 | 3 | 3 | 6 | 6 |
| L18 | 14 | 14 | 18 | 22 | 28 | 45 | 70 |
| B1 _{H9} | 4 | 4 | 5 | 5 | 6 | 10 | 12 |
| H1 | 12.5 | 12.5 | 16 | 18 | 24.5 | 35 | 43 |
| OD | 56 x 2 | 66 x 2 | 90 x 3 | 110 x 3 | 145 x 3 | 200 x 5 | 238 x 5 |
| V | 4 | 4 | 4 | 4 | 6 | 6 | 6 |
| Z | 45 | 45 | 45 | 45 | 30 | 30 | 30 |

Output Dimensions


**AD 047
ADR 047
ADS 047**




**AD 064 / AD 090
ADR 064 / ADR 090
ADS 064 / ADS 090**




**AD 110
ADR 110
ADS 110**



**AD 140 / AD 200
ADR 140 / ADR 200
ADS 140 / ADS 200**




**AD 255
ADR 255
ADS 255**



[unit: mm]

| Dimension | AD047 | AD064 | AD090 | AD110 | AD140 | AD200 | AD255 |
|------------------|-----------|-----------|---------|---------|------------|------------|----------|
| | ADR047 | ADR064 | ADR090 | ADR110 | ADR140 | ADR200 | ADR255 |
| | ADS047 | ADS064 | ADS090 | ADS110 | ADS140 | ADS200 | ADS255 |
| D1 _{H7} | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D2 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D3 _{H7} | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D4 _{H7} | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D5 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D6 | M3 x 0.5P | M5 x 0.8P | M6 x 1P | M6 x 1P | M8 x 1.25P | M10 x 1.5P | M16 x 2P |
| D8 _{H7} | 3 | 5 | 6 | 6 | 8 | 10 | 12 |
| D10 | 3.4 | 4.5 | 5.5 | 5.5 | 6.6 | 9 | 13.5 |

Max. Tilting Moment M_{2K}



$$M_{2K} = \frac{F_{2a} * Y + F_{2r} * (X+Z2)}{1000}$$

M_{2K} : [Nm]


F_{2a}, F_{2r} : [N]

$X, Y, Z2$: [mm]

| AD / ADR / ADS | 047 | 064 | 090 | 110 | 140 | 200 | 255 |
|----------------|------|------|------|------|------|-------|-------|
| Z2 [mm] | 37.9 | 46.2 | 63.1 | 75.5 | 92.2 | 119.2 | 148.8 |



Note : Applied to the output flange center at 100 rpm.

ADS-Permitted Radial and Axial Loads



The permitted radial and axial loads on input shaft of the gearbox depend on the design of the gearbox supporting bearings. APEX use the extension straddle oversized ball bearing design. It can take heavy load from both axes.


F_{1r} Radial Load
 F_{1a} Axial Load



If radial force F_{1r} is exert on the center of the output shaft $X=1/2 \times L$. The permitted radial load is given on above diagram.

If radial force F_{1r} is not exert on the center of the output shaft $X < 1/2 \times L$ or $X > 1/2 \times L$. The permitted radial and axial loads can be calculated by the position load factor K_b on the above diagram.

Selection of the optimum gear box



Recommended (for S5 Cycle Operation)

The general design is given for


$$\frac{J_L}{i^2} \leq 4 \times J_m$$

The optimal design is given for

$$\frac{J_L}{i^2} \cong J_m$$

J_L Load Inertia

J_m Motor Inertia



$$1. ED = \frac{t_a + t_c + t_d}{t_{cycle}} \times 100\%, t_{work} = t_a + t_c + t_d$$

Index : a. Acceleration, c. Constant, d. Deceleration, p. Pause (Eq.1)

$$2. i \cong \frac{n_m}{n_{work}}$$

n_m Output Speed of the Motor
 n_{work} Working Speed (Eq.2)

$$3. T_{2m} = \sqrt[3]{\frac{n_{2a} \times t_a \times T_{2a}^3 + n_{2c} \times t_c \times T_{2c}^3 + n_{2d} \times t_d \times T_{2d}^3}{n_{2a} \times t_a + n_{2c} \times t_c + n_{2d} \times t_d}}$$

(Eq.3)

$$4. T_{2max} = T_{mB} \times i \times K_s \times \eta$$

where K_s is

| K_s | No. of Cycles / hr |
|-------|--------------------|
| 1.0 | 0 ~ 1,000 |
| 1.1 | 1,000 ~ 1,500 |
| 1.3 | 1,500 ~ 2,000 |
| 1.6 | 2,000 ~ 3,000 |
| 1.8 | 3,000 ~ 5,000 |

T_{mB} Max. Output Torque of the Motor

η Efficiency of the Gearbox (Eq.4)

$$5. n_{2a} = n_{2d} = \frac{1}{2} \times n_{2c}$$

$$n_{2m} = \frac{n_{2a} \times t_a + n_{2c} \times t_c + n_{2d} \times t_d}{t_a + t_c + t_d}$$

$$n_{2N} = \frac{n_{1N}}{i}$$

(Eq.5)

$$6. F_{2m} = \sqrt[3]{\frac{n_{2a} \times t_a \times F_{2ra}^3 + n_{2c} \times t_c \times F_{2rc}^3 + n_{2d} \times t_d \times F_{2rd}^3}{n_{2a} \times t_a + n_{2c} \times t_c + n_{2d} \times t_d}}$$

$$F_{2am} = \sqrt[3]{\frac{n_{2a} \times t_a \times F_{2aa}^3 + n_{2c} \times t_c \times F_{2ac}^3 + n_{2d} \times t_d \times F_{2ad}^3}{n_{2a} \times t_a + n_{2c} \times t_c + n_{2d} \times t_d}}$$

(Eq.6)

Note



**APEX TAIWAN NORTH
ANDTEK AUTOMATION CO.,LTD**
TEL +886-02-82262655
13F-5, No.2, Jian 8th Rd., Jhonghe Dist., New
Taipei City 235, TAIWAN
sales@andtek.com.tw
www.apexdyna.com



**APEX TAIWAN CENTRAL
ANDTEK AUTOMATION CO.,LTD**
TEL +886-04-23594286
9F-6, No.925, Sec.4, Taiwan Blvd., Xitun Dist.
Taichung City 407 TAIWAN
sales@andtek.com.tw
www.apexdyna.com



**APEX TAIWAN SOUTH
MEN JENN ELECTRIC CO., LTD.**
TEL +886-06-237332 ~ 6
No.774, Zhonghua Rd., Yongkang Dist., Tainan
City 710, TAIWAN
menjenn@ms24.hinet.net
www.apexdyna.com



APEX DYNAMICS INC. SHANGHAI
TEL +86-21-69220577
No.128 ZHUHYING Road QINGPU Industry Area,
Shanghai, CHINA
sales@apexdyna.cn
www.apexdyna.cn



APEX DYNAMICS SHENZHEN, LTD.
TEL +86-755-84516325
No.1102A of D area, CFG mansion, Bao Yuan
Road, Bao'an District, Shenzhen, CHINA.
sales@szapexdyna.com
www.szapexdyna.com



APEX DYNAMICS BEIJING, LTD.
TEL +86-10-69570691
NO.1,YaoPingRoad.SongZhuang Town, Tongzhou
istrict, Beijing, CHINA.
bjapexdyna@163.com
www.bjapex.cn



CHONGQING APEX DYNAMICS CO., LTD.
TEL +86-23-67686860
406, Building 5, No.68,Jinyu Avenue, Beibu New
Area, Chongqing, CHINA
sales@cqapexdyna.com
www.apexdyna.com



APEX (XIAMEN) DYNAMICS TECHNOLOGY CO., LTD.
TEL +86-0592-720-5279
Unit B-3,1F.,No.129,Jingquan Road, Jimei District,
Xiamen, Fujian, CHINA
sales@xmmapexdyna.com
www.xmmapexdyna.com



APEX DYNAMICS USA, INC.
TEL +1-631-2449040
885 Marconi Avenue Ronkonkoma, NY 11779
U.S.A.
sales@apexdynamicsusa.com
www.apexdynamicsusa.com



APEX DYNAMICS KOREA INC
TEL +82-31-8179992
7-5, Aenigol-gil, Ilsandong-gu, Goyang-si, Gyeonggi-do,
Republic of Korea 10301
sales@apexdynakorea.co.kr
www.apexdynakorea.co.kr



APEX DYNAMICS JAPAN
TEL +88-092-4511202
1-3-46, Hamnichibasi, Hakata-ku, Fukuoka,
812-0897, JAPAN
sales@apexdyna.jp
www.apexdyna.jp



APEX DYNAMICS SINGAPORE PTE LTD
TEL +65-62-626228
3 South Buona Vista Road, #05-15 & #06-15.
SINGAPORE 118136
sales@apexdyna.com.sg
www.apexdyna.com.sg



APEX DYNAMICS (THAILAND) CO., LTD.
TEL +66-2-326623
87 Soi Ladkrabang 30, Ladkrabang, Ladkrabang,
Bangkok 10520, Thailand
Apexthai2010@gmail.com
www.apexdyna.co.th



APEX DYNAMICS BV
TEL +31-492-509995
Churchillaan 101 5705 BK Helmond, NETHERLANDS
sales@apexdyna.nl
www.apexdyna.nl



**APEX DYNAMICS
POLSKA SP. Z O.O.**
TEL +48-12-6304728
Ul. Krakowska 50, 32-083 Balice, Poland
sales@apexdyna.pl
www.apexdyna.pl



APEX DYNAMICS SPAIN, S.L.
TEL +34-93-6562990
Poligono Industrial Moli dels Freres, Calle C nº
12,08620 - Sant Vicenç dels Horts, Barcelona, SPAIN
apexdyna@apexdyna.es
www.apexdyna.es



LIMAN TRADING LIMITED FZC LLC
P.O. Box 97 , Postal Code 322, Corporate Parks,
Sohar Free Zoon, Oman



APEKS DINAMIK REDUKTOR DISLI SAN TIC AS
TEL +90-232-4589960
10053 SOKAK NO: 9 A.O.S.B. CIGLI – IZMIR– TURKEY
sales@apexdyna.com.tr
www.apexdyna.com.tr



APEX DYNAMICS AUSTRALIA PTY LTD.
TEL +613-95-852739
36 Taunton Drive, Cheltenham, Victoria 3192
AUSTRALIA.
sales@apexdyna.com.au
www.apexdyna.com.au



APEX DYNAMICS (I) JV
TEL +91-9607927142
Shop No. 02, S. No. 100/5, Pune-Satara Highway,
Ambegaon Khurd, Pune-411046 Maharashtra, India
sales@apexdyna.co.in
www.apexdyna.co.in



APEX DYNAMICS FRANCE SAS
TEL +33-160-135097
11 - Burospace - 91570 - Bièvres, France
info@apexdyna.fr
www.apexdyna.fr



APEX DYNAMICS SWEDEN AB
TEL +46-75-242444
Fredrikbergsgatan 2 SE-573 92 Tranås, SWEDEN
sales@apexdyna.se
www.apexdyna.se



PT.APEX DYNAMICS INDONESIA
TEL +62 21 2928 3681
Rukan Aralia Blok HY43 no.11, Harapan Indah II,
Bekasi - Jawa Barat, INDONESIA 17214
sales@apexdyna.co.id
www.apexdyna.co.id



APEX DYNAMICS GERMANY GMBH
TEL +49-7171 798069-0
Marie-Curie-Straße 25 D-73529 Schwäbisch Gmünd
wermerlanger@apexdynamics.de
www.apexdynamics.de



APEX DYNAMICS CZECH S.R.O.
TEL +420-577-663877
tř. Tomáše Bati 1851 765 02 Otrokovice ČESKÁ
REPUBLIKA
info@apexdynaczech.cz
www.apexdynaczech.cz



APEX DYNAMICS РОССИЯ
TEL +7-495-2255452
+7-495-6462422
г.Москва, ул. Южнопортовая, дом 7, строение
“С”, 3-й этаж
info@apexdynarussia.ru
www.apexdynarussia.ru



APEX DYNAMICS MIDLANDS LTD
TEL +44-0121-737-1170
Heath House, Cheadle Rd, Uxeter,
ST14 7BY, UK
mikeg@apexdynauk.com
www.apexdynauk.com



APEX DYNAMICS SWITZERLAND AG
TEL +41-55-4517020
Obergasse 40, CH-8854 Galgenen, Switzerland
info@apexdyna.ch
www.apexdyna.ch



APEX DYNAMICS MOTION (M) SDN BHD TEL
TEL +60 7237 1055
Block A1-2, #35-03, Mercu 1 Jalan Tanjung Puteri 1,
R & F Tanjung Puteri, Johor Bahru 80300, Johor.
sales@apexdyna.com.sg
www.apexdyna.com.sg



APEX DYNAMICS BRAZIL
TEL +55-47-30298700
Rua Senador Petrônio Portela, 47 - Bloco 5, Zona
Industrial Norte - CEP 89218-575 - Joinville (SC)
lucan@neoyama.com.br
adriano.duarte@neoyama.com.br
www.neoyama.com.br



APEX DYNAMICS ITALY SRL
TEL +39 02 36634521
VIA E. DE AMICIS, 2-20091 BRESSO (MI)
info@apexdynamics.it
www.apexdynamics.it



APEX DYNAMICS AUSTRIA GmbH
TEL +43 720788416
Dr. Hans-Lechner-Strasse 6,
5071 Wals-Siezenheim
info@apexdynamics.at
www.apexdynamics.at



UAB "APEKSO DINAMIKA"
TEL +370 52078165
Medaus g. 28A,
Medininku k., Vilnius r. Sav.
LT-13192
info@apexdyna.lt



APEX DYNAMICS DENMARK
TEL +45 73121260
Grundtvigs Allé 165, 6400
Sønderborg, Denmark
sales@apexdyna.dk
www.apexdyna.dk



APEX DYNAMICS ISRAEL
TEL +972-3-6470471
17 Hamefalsim St., Kiryat Arye,
Petach-Tikva 4951447
Sales@apexdynamics.co.il
www.apexdynamics.co.il



APEX DYNAMICS SLOVAKIA S.R.O.
TEL +421919400476
Trenčianska cesta 887/52, 957 01
Bánovce nad Bebravou, Slovak republic
office@apexdyna.sk
www.apexdyna.sk



APEX DYNAMICS, INC.

No10. Keyuan 3rd RD.Situn District, Taichung City 40763, Taiwan (R.O.C)

Tel:886-4-24650219 | Fax:886-4-24650118

sales@apexdyna.com | h?p://www.apexdyna.com

APEX-2021-09-AD/ADR/ADS SERIES-1.0-TWN

Printed in Taiwan

